

18" x 18" Canopy Luminaire **MC1005i**

Uses/Function

Combines strength-gaining design with energy saving technology. Architecturally angled facets with smooth corners provide an even distribution of light ideal for parking garage applications.

Design

- Heavy duty die-cast
- Lens is clear prismatic polycarbonate and UV stabilized
- UL 1598 listed for damp locations when wall mounted or in covered ceiling applications
- Die-cast back housing, chromate conversion coating, color matched vandal resistant polycarbonate front housing with clear ribbed area



Dimensions

17.8"L x 17.8"W x 13.58"D

Specifications/Options

• Lamp Life: 100,000 hours		
• Wattage:		
Lamp	(System)	Replaces HID
40	(43)	100w
65	(69)	125w
80	(86)	175w
100	(106)	200w
120	(126)	250w
150	(157)	300w
200	(210)	400w

- **Voltages :** 120, 208, 220, 240, 277, (480 special order)
- **Color Temp:** 3500k, 4100k, 5000k
- **Finish:** Bronze, Black, White, or Custom

Induction Lighting Benefits

- Long Life - 100,000 hours
- Color rendering - 85 CRI
- Color Temperatures - 3500k, 4100k, 5000k
- Energy Efficient - High Output/Less wattage
- Longer Lumen maintenance - Slower degradation
- Consistent color- Minimal color shifting
- Maintenance costs - lasts 15+ years without change out
- Instant On - Can control with photocell and motion sensor
- No Flickering. No Strobging. No Noise
- Operating ambient temperature
-30°C (-22°F) ~ +40°C (+104°F)